

Reg. Off.: 101/A, "Shreyans", Kesar Baug CHS Ltd., L. T. Road, Borivali (W), Mumbai 400092. Maharashtra, India.
 Corp. Off.: 509, HIVE 67, ICON Tower, Borsapada Road, Next to Raghuleela Mall, Kandivali (W), Mumbai 400067 M.S. India
 Fac. Add.: Plot No. 1, Dewan & Sons Udyog, Vill. Mahim, Tal. & Dist Palghar 401404. Maharashtra, India.

DATE: October 2, 2024

TECHNICAL DATA SHEET

PRODUCT CODE : MPRL LUBEOL - 500

PARAMETERS	TEST METHOD	STANDARD	TYPICAL RESULT
Appearance	Visual	B & C	B & C
Specific Gravity, @ 29.5 °C	ASTM D 1298	0.885 - 0.915	0.900
Color	ASTM D 1500	1.0 Max	L 0.5
Aniline Point, °C	ASTM D 611	90 - 100	94
Flash Point, COC, °C	ASTM D 92	200 Min	210
Kin. Vis. @ 40 °C CST	ASTM D 445	90 - 110	101.472
Kin. Vis. @ 100 °C CST	ASTM D 445	07 - 11	9.241
Viscosity Index	ASTM D 2270	40 - 50	42
Pour Point (°C)	ASTM D 97	-30 Max	-33

Analytical Chemist: _____
(Quality Control Department)
MEHTA PETRO-REFINERIES LTD.